

ELEVATOR PRODUCTS ENGINEERED AND BUILT FOR RELIABILITY



*Your Trusted Partner in the Elevator Industry*



## Three Phase Drive Isolation Transformer



### Standard Features

- Approved for Elevator Applications
- UL Listed Nomex Insulation System
- Primary Voltage Range 208-600VAC
- Secondary Voltage Range 120-600VAC
- Delta/Wye Configuration
- 60 Hz Frequency
- (1) 5% FCAN and (1) 5% FCBN Voltage Tap
- 3-6% Impedance
- 200°C Insulation System (130°C rise)
- Elevator Duty Rated
- Stackable Heavy Duty Ventilated NEMA Type 1 Enclosure
- ANSI 61 Gray Color
- Copper or Aluminum Coil Designs

### Options

- 220°C Insulation System (150°C rise)
- 80°C rise or 115°C rise
- Input/Output Protection
- Sprinkler Proof Enclosure
- Tip Jacks
- K Ratings of 9, 13 and 20 Available
- Electrostatic Shields
- Custom Enclosures Available
- 50 Hz Frequency
- Auxiliary Outputs Available

Ratings		
KVA Ratings*	H.P. Ratings	Enclosure (in inches)
11	7.5	34H x 26W x 24D
14	10	
20	15	
27	20	
34	25	
40	30	
51	40	34H x 36W x 24D
63	50	
75	60	
93	75	43H x 36W x 30D
118	100	
145	125	
175	150	51H x 44W x 36D
220	200	
275	250	
330	300	
440	400	Special - Call Warner Power for Details
550	500	

\*Other KVA Ratings Available

## DC Filter and Choke Assembly



### Standard Features

- CSA Certified
- UL Listed Insulation System
- 5 mH Inductance Value
- Filter Board Assembly
- 360 Hz Ripple Frequency
- 180°C Insulation System (115°C rise)
- Elevator Duty Rated
- Stackable Heavy Duty Ventilated NEMA Type 1 Enclosure
- ANSI 61 Gray Color
- Copper or Aluminum Coil Designs

### Options

- 220°C Insulation System
- 150°C Temperature Rise
- 2.5, 3, & 6 mH Inductance Values
- Input/Output Protection
- Custom Paint Colors

Current Rating	Height (inches)	Width (inches)	Depth (inches)
25	28.50	25.00	24.00
50/100/150/200/250/300	34.00	36.00	24.00
350/400	43.00	36.00	30.00
450	51.00	44.00	36.00

